

PIR-rörelsesensor, temperatur och ljus nivå setting,
reläutgång, M485, Modbus RTU, DCON, 10 - 30VDC.
Inomhus

FEATURES

- Rörelsesensorn ljusdetektering, temperaturgivare för energistyrning
- Ansluter energihushållning, lokal-belysning styrning via RS485-porten
- Med kraftfull inbyggt relä för enkel ljus aktivering 250VAC (1500 Watt T8)
- 360 ° rörelsedetektor - upp till 8 m i diameter och 4 meter höjd
- Tidsfördröjning / Känslighet är justerbar
- temperatursensor, - mätning av rumstemperatur eller brandlarm
- Reläutgång för att slå på ljuset via PIR / ljus-styrka och temperatursensorer
- RS485 två-trådskommunikationsbussen
- DCON och Modbus RTU protokoll
- loft monterad design
- Försörjningsspänning: 10 - 30VDC ca. 2W
- Dimensioner: Ø121 x 52 mm
- IP20





SPECIFICATIONS

Serial	:	1x RS-485 DCON, Modbus RTU
Driftstemperatur	:	0 to +35°C
Övrig	:	Hardware: 8-step Switch-selectable (seconds): 6, 16, 33, 66, 131, 262, 524, 1049 Software: 16-step (seconds): 2, 4, 6, 8, 16, 33, 49, 66, 131, 262, 393, 524, 1049, 2097, 3146, 4194
IP-Tæthed	:	IP20
Luftfugtighed	:	10 to 90% RH, Non-condensing
Lysstyrke	:	Hardware: 2 mode (Dawn and dust) / Software: 5-step
Montering	:	Ceiling mounting
Relæ	:	1x Power Relay, Form C; NO: 10 A @ 250 VAC NC: 6 A @ 250 VAC
Strømforsyning	:	10 to 30 VDC (1.3 W)
Temperatur	:	Measurement Range: -25 ~ +100°C Accuracy: ±2°C
Range	:	Distance: 4 meters Max. 360°; Diameter 8 meters Max.
Dimensioner	:	121 mm x 52 mm

