



Svensk Binär Teknik

MOD-GSM-4G

4G-modul LTE RS232 RS485 Modbus RTU TCP LTE-FDD WCDMA GSM Trådlös Transparent Transceiver Modem

FEATURES

AT-kommandeeredon kommunikation
Bandwidth 1.4/3/5/10/15/20MHz
LTE-FDD: B1 / B3 / B7 / B8 / B20 / B28A
WCDMA: B1 / B8
GSM: B3 / B8
Input DC 8V-28V
arbetstemperatur -30 °C -70 °C
Mått 82 × 84 × 24 mm
Max uppströms hastighet 50Mbps
Max nedströms hastighet 150Mbps
RS485 / RS232



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



SPECIFICATIONS

Driftstemperatur	:	-30°C- +70°C
Antenne	:	SMA
Baudrate	:	Max 921600bps□default 115200bps
Frekvens	:	1.4/3/5/10/15/20MHz
Porte	:	RS485 / RS232
Protokol	:	TCP/UDP/PPP/FTP/HTTP/NTP/PING/QMI/NITZ/CMUX/HTTP S/SMTP/MMS/FTPS/ SMTPS/SSL/FILE
Strømforbrug	:	20mA idle
Strømforsyning	:	DC 8V~28V
Dimensioner	:	82×84×24mm

