

Embedded PC, Pentium® N4200 upp till 2,50 GHz, 4x
RS-232/422/485, 9~48VDC

FEATURES

- Pentium® Processor N4200
- 1xDDR3L SO-DIMM max. upp till 8GB
- Triple Independent Display (1x CDS, 1X VGA, 1X DisplayPort)
- 1x 2,5 "SATA Drive Bay, 1X MSATA-uttag
- Rik I/O (2x LAN, 4x USB, 4x Com, 8x Isolerad Dio)
- 2x Full storlek Mini-PCIe Expansion Socket
- Stödjer 2x Poe + -funktion (med option modul)
- Stöder tändsavgänningsfunktion (IGN) (med option modul)
- Stödjer CD-teknik för konvertibel Panel PC
- Inbyggd två 2W interna högtalare
- 9~48VDC via 3-pin Terminal Block





SPECIFICATIONS

CPU	:	Intel® Pentium® N4200
USB	:	4x USB 3.0 (Type-A)
Driftstemperatur	:	-40°C to 70°C
Antenne	:	4x Antenna Holes
Forsyning	:	9~48VDC via 3-pin Terminal Block
Grafik	:	Integrated Intel® HD Graphics 505
Hukommelse	:	1x DDR3L 1333/1600/1866 MHz 204-Pin SO-DIMM Socket (8GB max)
Lyd	:	Realtek ALC888-GR
Montering	:	Wall / VESA / CDS / DIN Rail
Msata	:	1x mSATA Socket (SATA 3.0, Shared by Mini-PCIe Socket)
Netværk	:	2x GbE LAN Intel® I210
OS SUPPORT	:	Windows 10





Svensk Binär Teknik

EPC-N4200-CDS

SPECIFICATIONS

SIM kort	:	1x SIM Socket
Vikt	:	1.49 kg
Dimensioner	:	204.5 x 149 x 41.5 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.