

MON17-OPEN-800NITS

17 "OpenFrame TFT 800Nits solljus läsbar, 12VDC SXGA 1280x1024, låg strömförbrukning FEATURES

- 17 "TFT
- Solljus Readable
- LED Bakgrundsbelysning
- SXGA (1280x1024) High Definition
- High Shock Vibration Resistance
- Låg strömförbrukning
- Bred dimning
- 358.5x296.5x20.5mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

Driftstemperatur	:	0°C ~ +50°C
Övrig	:	OPTIONS!: Need to be ordered special! Touch, S-video/Component/Audio
Antal farver	:	16.7M
Betragningsvinkel	:	170(H)x, 160(V)
Forsyning	:	12VDC
Indgang	:	VGA, DVI, HDMI
Kontrast	:	1000:1
Lysstyrke	:	800 cd/m2
Opløsning	:	1280x1024 (SXGA)
OSD	:	Brightness, Contrast, H/V Position, color, Phase, Clock
Pixels	:	0.264(H)x0.264(V) (mm), Pixel Pre Inch (PPI) 96
Skærm	:	17" TFT LCD LED Backlight 800nits SXGA





Svensk Binär Teknik

MON17-OPEN-800NITS

SPECIFICATIONS



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.