

12.1 "Industrial Panel PC, I3 / I5 CPU, USB, RS232,
tryck på, 450/500/1000 nits versioner, 9 ~ 36VDC
leverera många alternativ!

FEATURES

12.1 "TFT

CPU Gen.6 i3 Standard (I5-alternativ)
med eller utan beröringsresistiv, projicerad
kapacitiv 7h anti scratch yta
1 x 260-pin SO-DIMM DDR4 2100MHz max. 16GB
2 x USB 3.0
1x 2½ "SSD Sata Bay
1 x Mini PCIe Slot Full storlek
1xDB9 RS232 / 422/485, COM1, 1X RS-232 dB9 Com
2
2 x RJ45 GBE LAN RJ45
IP66 Front
Vesa Mount 100x100
319x245x51.7mm
1 x 3 Pin DC 9 ~ 36VDC
Windows IOT Support





IPP12-IX-1000N

SPECIFICATIONS

USB	:	2 x USB 3.0 type A
Driftstemperatur	:	0~50°C / -20~60°C (option)
Back-up	:	UPS battery 21W/10.8W/1.95Ah OPTION!
Approval	:	CE / FCC, Class A / UL
Ethernet	:	2 X RJ45 GbE
Forsyning	:	DC 9~36Vdc MAX 47W
Kontrast	:	1500:1(800x600), 1000:1(1024x768) (1000 nits 700:1)
Lyd	:	line out
Montering	:	Panel Mount, Vesa mount 100x100
Opløsning	:	MAX 800x600 /1024x768
OS SUPPORT	:	Windows IOT
Porte	:	1 x DB-9 RS-232/422/485, COM1 (Default RS-232) 1 x RS-232 DB-9, COM2





Svensk Binär Teknik

IPP12-IX-1000N

SPECIFICATIONS

Touch	:	Needs to be ordered! Resistive, Projected capacitive or glass
Vikt	:	2.6Kg
Dimensioner	:	319x245x51.7mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.