

Fläktlöst system, 9:e/8:e generationens i7/i5/i3
Celeron®-processor, Intel® H310, USB, RS232, VGA,
HDMI, DIN-MOUNT

FEATURES

Industriell fläktlös Celeron, i3/i5,i7 CPU-stöd (LGA 1151)
Gen. 8/9
1x RS232/422/485. FRIVILLIG! ISOLERAD RS232/422/485, Måste beställas separat!
4 USB 3.1 Gen. 1
2 x USB2.0
1 x USB (intern, 180D typ A för licensnyckel, upp till 30 mm)
2 x ETH Intel i211-AT & i219-LM (Tillval! fler kan beställas)
VGA, HDMI-utgång
19~30VDC
OPTION: väggfäste eller DIN-fäste
83,4x192x230 mm (BxHxD)
Arbetstemperatur -10°C till +60°C, OBS Kräver RAM OCH SSD även specificerat för -10°C till +60°C
Beställ separat!
OS stöder Windows 10 och Linux





SPECIFICATIONS

CPU	:	9th/8th gen Intel® Core™ processor, up to 65W
Chipset	:	Intel® H310
USB	:	4 x USB 3.1 Gen1 2 x USB 2.0 1 x USB 2.0 (internal, 180D type A for license key, up to 30mm)
Driftstemperatur	:	-10°C to +60°C (+14°F to +140°F) with Intel®, 9th/8th gen Intel® Core™ and W.T. HDD/SSD
BIOS	:	AMI
Approval	:	CE/FCC
Ethernet	:	2 x 10/100/1000 Mbps (Intel® i211-AT & i219-LM) OPTION! More LAN ports available from extension I/O modules
Hukommelse	:	2 x DDR4-2666/2400 MT/s un-buffered SO-DIMM, up to 64GB
Materiale	:	Aluminum extrusion heavy-duty cold-rolled steel
Montering	:	Wall mount as option, DIN mount as option
Mål og vægt	:	Weight (net/gross) 3.82 kg (8.43 lb)/4.78 kg (10.55 lb)
OS SUPPORT	:	Windows® 10, Linux





Svensk Binär Teknik

EPC-IX-2E1S6UHV-DIN

SPECIFICATIONS

Spænding	:	Type: ATX/AT Input: 24 VDC (uMin=19V/uMax=30V)
Udgange	:	1 x VGA 1 x HDMI
AMT	:	12
Dimensioner	:	Dimensions (W x H x D) 83.5 x 192 x 230 mm (3.28" x 7.54" x 9.04")



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.