

EPC-CEL-3G2S1DP1H

Embedded PC, Celeron J6412, DIN-rail, 3x LAN, 2x COM, 6x USB

FEATURES

- Intel Celeron J6412 Quad Core 2,0 GHz
- 1x DDR4L 3200MHz Max upp till 32GB
- 3x GbE LAN Intel® 225-V
- 2x RS-232/422/485
- 1x M.2 SATA, 1x 2,5" SATA
- 1 x DP, 1 x HDMI
- WiFi/Bluetooth/4G/5G (tillägg)
- DC-ingång 9V~36V
- Arbetstemperatur -20°C ~70°C
- Windows 10/11, Linux



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

SPECIFICATIONS

CPU	:	Intel® Elkhart Lake Celeron J6412 2.0GHz , TDP 10W
USB	:	2 x USB2.0 / 4 x USB3.0
Serial	:	2 x RS-232 / 422 / 485
LAN	:	3x GbE supporting Wake-on-LAN and PXE
Driftstemperatur	:	-20~70°C (-4~158°F)
DIO	:	DIO 8 Bits (4 In / 4 Out) Optional
Forsyning	:	Power Input 9~36VDC
OS SUPPORT	:	Windows 10 / 11 □ Linux, Ubuntu
RAM	:	DDR4L MAX 32GB
WiFi	:	Optional □WiFi / Bluetooth / 4G / 5G)
Vikt	:	1.5 Kg
Dimensioner	:	185 x 145 x 57 mm





Svensk Binär Teknik

EPC-CEL-3G2S1DP1H

SPECIFICATIONS



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.