



IPP19-J1900

PanelPC, IP65 front med Capacitive touch och J1900 quad core CPU

FEATURES

- 19" TFT-LCD 250 nits
- Upplösning: 1280x1024
- Frontpanel IP65
- Intel® Celeron® J1900, fyrkärnig, upp till 2,42 GHz
- 4GB RAM ombord
- 2 x RJ45
- 1 x HDMI
- 4 x USB2.0
- 6 x RS-232 (2x DB9, 4x terminal)
- 9-36V DC 3-polig plint
- 20 ~ 60° C arbetstemperatur
- Panelmontering/ 75 mm VESA-montering
- Mått 437,27 x 316,27 x 60,3 mm





IPP19-J1900

SPECIFICATIONS

CPU	:	J1900,Quad-core, Up to 2.42GHz
Memory Type	:	DDR3
Max. Memory Capacity	:	8
Power Input	:	DC 12~36V
USB	:	4 x USB 2.0
Serial	:	2x DB9 RS232, 4x screw terminal RS232
Driftstemperatur	:	-20° C ~ +60° C
Ethernet	:	2 x GbE LAN RJ45
Hukommelse	:	8GB MAX
Lysstyrke	:	250 nits
Opløsning	:	1280 x 1024
OS SUPPORT	:	Windows 10 / Ubuntu / CentOS





Svensk Binär Teknik

IPP19-J1900

SPECIFICATIONS

Skærm	:	19" TFT-LCD
Antal Video Udgange	:	1
Antal LAN Porte	:	2
Antal USB	:	4
Antal Serial	:	6



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.