

19" Panel PC IP65 front, Celeron, I5 eller I7, 2xCOM, 2xRJ45, 9~36Vdc, 10Bit GPIO, FEATURES

19" TFT-LCD Panel PC
IP65 fram
Upplösning: 1280*1024
250 nits
5-tråds resistiv pekskärm (kapacitiv touch på begäran)
Intel Celeron J4125/J6412 CPU / Core i5 /i7
RAM: 1x SO-DIMM DDR4 (celeron) max 16 GB, i5/i7 2x SO-DIMM DDR4 max 32 GB
1 x M.2 2242/2260/2280 SATA
1 x SATA (2,5 tum SATA)
1 x M.2 2280 NVME
MPCle: M.2 3042/3052 för 3G/4G/5G med inbyggd SIM-kortplats, M.2 2230 WiFi & BT
2x RJ45 Intel i225V (på särskild begäran kan ytterligare 2 läggas till)
USB: Celeron version: 4*USB2.0+2*USB3.0 (J4125/J6412), i5/i7 version 4*USB3.0+2*USB2.0
COM: 2x DB RS-232/422/485-port, 4*RS232 i expansionsport
GPIO: 1* 10 bitars GPIO Inuti expansionsporten
Strömförsörjning: 9-36V DC-kontakt
Arbetstemperatur: Med luftflöde -10 ~ 60° C
Antivibration med SSD: 3 Grms, IEC 60068-2-64, slumpmässigt, 5 ~ 500 Hz, 1 timme/axel
Anti-chock med SSD: 30 G, IEC 60068-2-27, halv sinus, 11 ms varaktighet
437,27x361,27x68,8mm
OS-stöd: Windows 10 / Ubuntu, CentOS





SPECIFICATIONS

Memory Type	:	DDR4
Max. Memory Capacity	:	16
Power Input	:	DC 9~36V
Antal Video Udgange	:	1
Antal LAN Porte	:	2
Antal USB	:	6
Antal Serial	:	2

