



Svensk Binär Teknik

WLAN-AP3000AX-WALL

Wi-Fi 6 Dual Band Wireless Access Point 3000 Mbps med PoE och 2 LAN-portar

FEATURES

- Dual Band 802.11ax 3000 Mbps Takmonterad trådlös åtkomstpunkt
- Max. trådlös hastighet på 2400Mbps (5GHz) & 600Mbps (2,4GHz)
- Stöder upp till 256 samtidiga klientanvändare
- 2 x 10/100/1000BASE-T RJ45-port
- 4 x intern 4dBi-antenn (2,4G x2, 5G x2)
- Lägen: AP, Gateway, Repeater
- WPA3 / WPA2 / WPA-stöd
- Takfäste
- Mått: 185,82 x 185,82 x 36,6 mm
- Stöder 48V DC PoE och 12V DC-ingång
- Drifttemperaturområde: -20 till 55°C
- Vikt: 380 g



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.



SPECIFICATIONS

LAN	:	2 x 10/100/1000BASE-T RJ45 port
Antal	:	256 clients (200 is suggested, depending on usage)
Antenne	:	4 x Internal 4dBi antenna (2.4G x2, 5G x2)
Båndbredde	:	20MHz, 40MHz, 80MHz, 160MHz
Forsyning	:	48V DC IN, 0.5A, IEEE 802.3at PoE+ (WAN/PoE were changed port) 12V DC IN, 1.5A from DC Jack (5.5 x 2.1mm)
Modes	:	Access Point Gateway Repeater WISP Mesh
Montering	:	Ceiling Mount
Sikkerhed	:	WPA3 Personal, WPA2/WPA3 Personal, WPA2 Personal (AES), WPA2 Personal (TKIP), WPA2 Personal (TKIP+AES), WPA/WPA2 Personal (AES), WPA/WPA2 Personal (TKIP), WPA/WPA2 Personal (TKIP+AES), WPA2 Enterprise, WPA/WPA2 Enterprise
Dimensioner	:	185.82 x 185.82 x 36.6 mm

