



KVM4-HDMI-MATRIX

4-portars KVM-switch, matris 4K 60Hz HDMI, 2 x USB 3.2, 4 x USB 2 (HID) med USB-roaming, PIP etc. FEATURES

- 4-portars KVM-switch/matris med USB-roaming
- Ingång HDMI 2.0 x 4 (enkel video x 4 datorer) / USB 3.2 Gen 1 typ B x 4
- Utgång HDMI 2.0 x 2 (enkel video x 2 datorer) / USB 3.2 Gen 1 typ A x 2 (bak och fram)
- 4K 4096x2160@60Hz (4:4:4) / 3840x2160@60Hz (4:4:4)
- EDID-hantering
- Stöder 16:9-, 21:9- och 32:9-skärmar
- Vertikal PBP med 2 x 32:9-skalning
- Dubbelt utgångsläge för 2 skärmar
- Manuell växling, Snabbtangenväxling, Seriella kommandon
- Musroaming (musmarkören flyttas till en annan skärm/dator)
- Ljudjackingång
- Nätaggregat: 9-12 VDC ingår
- Mått: 40 x 220 x 130





SPECIFICATIONS

Serial	:	RJ11 x 1 (Baud Rate = 19200bps) 8-Bands Baud Rate Selections Mini USB x 1 (Any Baud Rate)
Driftstemperatur	:	0~40°C, Humidity<80%
Forsyning	:	DC 9~12V
Input	:	HDMI 2.0 x 4 (Single Video x 4 PCs) USB 3.2 Gen 1 Type B x 4 Audio Jack in x 4
LED	:	Status x 1 Port Status LED x 4
Modes	:	Picture by Picture Mode Monitor by Monitor Mode (Dual Monitor Mode) (MbM Mode)
Output	:	HDMI 2.0 x 2 (Single Video x 2 PCs) USB 3.2 Gen 1 Type A x 2 (Rear & Front) USB HID Type A x 4 (Rear & Front) Audio Jack out x 1 Audio In x 1 (Embed to Port A)
Resolution	:	4096x2160@60Hz (4:4:4) 3840x2160@60Hz (4:4:4)
Number of Buttons	:	Port Select x 4 Function x 1 Video Swap x 1 Console Swap x 1 Sync x 1
Display	:	Support 16:9, 21:9, 32:9 Displays
Dimensioner	:	40 x 220 x 130mm

