



IPP12.1-J6412-WIDE

12,1" fläktlös PC-dator IP65 front12,1" LCD-skärm,
1280 x 800, LED 400 nits, Intel® Celeron J6412
widescreen

FEATURES

12,1" LCD 1280 x 800 LED 400 Nits
Intel® Celeron J6412-processor Intel® Elkhart Lake
BISO UEFI
Stöd DDR4-2666/2933/3200MHz, Max. Kapacitet
32GB
2 x HDMI
3 x USB 3.0
3 x USB 2.0
2 x LAN
1 x Line-out
1 * M.2 Key-M(NVMe SSD 2280), 1 * M.2 Key-B Slot
Säkerhetsstöd TPM 2.0 inbyggd IC
Standard IP66/IP67-modeller I/O: 1 x HDMI, 2 x
USB, 1 x LAN.
(Behöver beställas special: kontakttyp: M12
metallkontakter, MIL-38999, MIL-26482
seriekontakter
-15°C ~ 70°C (5°F ~ 158°F), 10% ~ 90% (ingen
kondensation)





Svensk Binär Teknik

IPP12.1-J6412-WIDE

SPECIFICATIONS

Memory Type	:	DDR3
Max. Memory Capacity	:	32
Power Input	:	DC 12V
Antal Video Udgange	:	2
Antal LAN Porte	:	2
Antal USB	:	6



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.