



Wi-Fi 6 AX1800 Dual Band VPN-säkerhetsrouter med PoE+ som option

FEATURES

Nästa generations Wi-Fi 6 (802.11ax) med hastigheter upp till 1,8 Gbps
Dubbelband (2,4 GHz och 5 GHz) med MU-MIMO för miljöer med hög densitet
Robusta VPN-funktioner: IPSec, SSL, PPTP, L2TP, GRE (upp till 60 tunnlar)
Inbyggd SPI-brandvägg, DoS/DDoS-skydd, innehålls- och IP-filtrering
Dubbelt WAN med redundans, lastbalansering och stöd för hög tillgänglighet
Central AP-kontroller med captive portal och RADIUS
Option PoE+-version med 4-portars 802.3at PoE och PD Alive Check (tillval)
Enkel implementering via installationsguide, instrumentpanel och fjärrhantering





SPECIFICATIONS

Driftstemperatur	:	0°C to 50°C; fanless design
Övrig	:	Built-in AP controller with captive portal and RADIUS
Firewall	:	SPI Firewall, DoS/DDoS protection, NAT, MAC/IP filtering, Content Filtering, WPA3 support
Porte	:	5 x Gigabit RJ45 (1 WAN, 1 LAN/WAN, 3 LAN)
Standarder	:	IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6), dual-band 2.4GHz + 5GHz
Material	:	Metal housing, 1U height, desktop or rack-mountable
WiFi	:	Up to 600Mbps (2.4GHz) + 1200Mbps (5GHz)
WWAN	:	Dual-WAN failover, load balancing, high availability

