

EPC-I7G14-2S2L4UDH

Fläktlöst stöd för Intel® 14:e/13:e/12:e generationens Core™ 35W CPU, 2xCOM 8xUSB, 2xLAN, HDMI, DP, DIN-montering, DC 12~24V

FEATURES

CPU Intel® 14:e/13:e/12:e kärnan™ LGA1700-sockel (max. 35 W)
 RAM 1 x 262-pin DDR5 SO-DIMM 4800/5600 MHz SDRAM MAX 32 GB
 Intel® H610E, integrerad Intel® UHD-grafik 730/770
 1 x 2,5 GbE-portar 2 x GbE-portar (1 x Intel® i226LM, 1 x Intel® i219LM, 1 x Intel® i210AT)
 Vakthundstimer
 TPM: dTPM 2.0
 2xCOM (1x RS232, 1x RS232/422/485)
 8x USB (2 x USB-A 3.2 Gen2 (10 Gbps) 2 x USB-A 3.2 Gen1 (5 Gbps) 2 x USB-A 2.0 2 x intern USB-A 2.0)
 1 x M.2 E-nyckel 2230-kortplats (PCIe 3.0 x1 + USB 2.0 + CNVi)
 1 x mPCIe (PCIe 3.0 x1 + USB 2.0, full storlek) med 1 x nano-SIM-kortplats
 1 x DisplayPort 1.4 (DP++), upp till 4096x2304@60Hz
 1 x VGA, upp till 1920x1200 vid 60Hz
 1 x M.2 M-nyckel 2242/2280-kortplats (PCIe 4.0 x4 + SATA)
 Vägghäggmontering (standard), DIN-skene (tillval med CTOS-fäste)
 -20 ~ 60 °C, omgivningstemperatur med luftflöde
 CE, FCC klass A
 Mått (B x D x H) 55 x 164 x 210 mm
 DC 12~24V via 2-polig kopplingsplint, max. 80W
 OS-stöd: Windows 10 / Windows 11 / Ubuntu



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

SPECIFICATIONS

CPU	:	Intel® Core™ i3-12th Gen
CPU	:	Intel® Core™ i3-14th Gen
CPU	:	Intel® Core™ i5-12th Gen
CPU	:	Intel® Core™ i5-14th Gen
CPU	:	Intel® Core™ i9-12th Gen
CPU	:	Intel® Core™ i9-14th Gen
CPU	:	Intel® Core™ i9-13th Gen
CPU	:	Intel® Core™ i5-13th Gen
CPU	:	Intel® Core™ i3-13th Gen
Memory Type	:	DDR5
Max. Memory Capacity	:	32
Graphics	:	Integrated Intel® UHD Graphics 730/770



SPECIFICATIONS

Expansion	:	1 x nano SIM card slot
Power Input	:	DC 12~24V
Max. Power Consumption	:	170W
USB	:	2 x USB-A 2.0
USB	:	4 x USB-A 3.2
Serial	:	1x RS232
Serial	:	1 x RS232/422/485
LAN	:	2x 1Gb LAN
LAN	:	1x 2.5Gb LAN
Driftstemperatur	:	-20 ~ 50°C
Storage Temp.	:	-30 ~ 70°C



SPECIFICATIONS

Vibration	:	5~500Hz 3 Grms
Shock	:	10G peak acceleration (11 m sec. duration), operation
Shock	:	30G peak acceleration (11 m sec. duration), nonoperation
Shock	:	According to IEC 68-2-27
Vikt	:	2.5KG
Dimensions	:	55 x 164 x 210mm
Certification	:	CE/FCC Class A
Antal Video Udgange	:	2
Antal LAN Porte	:	3
Antal USB	:	6
Antal Serial	:	2

