

Web baserad relämodul med 24 reläutgångar. 18 x Power relä 250VAC / 5A COM, NO, NC. 6 x COM, NO, NC. 10-30VDC.

FEATURES

- Ethernet-baserad relämodul med Modbus med I/O-parfunktion
- Digitala signaler speglas på en annan modulutgångar
- Power Relay, 250Vac, 30VDC, 5A DIN
- Spänning : 10 - 30VDC, 3 Watts
- Mått: 180 x 111 x 70 mm
- Driftstemperatur: -25 - +75°C





Svensk Binär Teknik

ETH-MOD24

SPECIFICATIONS

Stik	:	Skrueterminaler
Udgange	:	8 relæer Type A (slutte) AC: 240 V/ 3 A DC: 24/ 3 A Lukketid: 15 ms Åbnetid: 3 ms 6 relæer type C (Skifte) AC: 240 V/2 A DC: 24V/ 2 A Lukketid: 5 ms Åbnetid: 5 ms
Dimensioner	:	70 x 180 x 111 mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.