

ETHIO-R10I10

10 x digital in, 10 x digital ut - I / O-styrenhet via
Ethernet eller RS485, 9 - 24VDC

FEATURES

- Distribuerad I/O via Ethernet/RS485
- Kan styras via RS485 eller Ethernet
- 10 x digital in 10 x relä ut (mekaniskt relä)
- 9VDC ~ 24VDC matningsspänning (strömadapter ingår)
- 16bit / 100MHz CPU
- 256 KB ROM, 1 MB SDRAM



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk



SPECIFICATIONS

CPU	:	16 bit CPU, 100 MHz
Driftstemperatur	:	0-55°C
Ethernet	:	1 x 10/100 Mb/s - Auto-crossover detection
Forsyning	:	9 ~ 24VDC, 0,5 ~ 1A
Hukommelse	:	1 MB
Input	:	10 digitale inputs, Optocoupler isolation: 2500VDC, Voltage overload protection: 70VDC
Kabinet	:	Stålkabinet i format 30 x 81 x 103 mm. (H x B x D)
Output	:	10 digitale outputs, Optocoupler isolation: 2500VDC, Relay: 30VDC 1A
Porte	:	Tilslutning af RS232/485 via skrueterminal Hastigheder fra 1200 bps til 230 kbps
Protokol	:	TCP/IP, UDP, DHCP, HTTP, TELNET, ARP, ICMP, PPPoE, DDNS, SMTP
Skærm	:	Viser: Power, Netværk, RS485 status, IO status,
Stik	:	1 x RJ45 til Ethernet samt skrueterminaler





Svensk Binär Teknik

ETHIO-R10I10

SPECIFICATIONS

Dimensioner : 135 x 115 x 35mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.