



Inbyggd DNV maringodkänd PC, 3 x RS422/485 Isolated, D2550 1,86GHz, 2 x Gbit

FEATURES

Design för industriell automation, M2M-lösningar
Inbyggd Atom Dual Core D2550 1,86 GHz-processor
1 x DDR3 SODIMM, max. 4 GB
3 x RS422/485-kommunikation med isolationsskydd
Stöd för 8 GPIO av Phoenix-typ terminalblock
2x Giga LAN, 2x USB, 1x VGA, 1x Linjeingång,
Linjeutgång, Micro I
Fläktlös, högeffektiv termisk design, vikt/tätad
konstruktion
Operativsystemstöd: Windows 7 32/64-bitars,
Windows 10 32/64-bitars,
1,5 kV DC-isolationsresistans DNVGL-CG-0339, IEC
60945 4:e etappen, CE/FCC



SPECIFICATIONS

CPU	:	Intel® Atom Dual Core D2550 1.86 GHz
Chipset	:	Intel NM10
USB	:	4 x USB 2.0 by pin-header(internal) ; 2 x USB 2.0 (external)
Driftstemperatur	:	-15 to 55 deg.C
Approval	:	DNVGL-CG-0339, IEC 60945 4th Edition, CE / FCC
Chok/Vibration	:	Anti-Vibration 5Hz~500Hz /1Grms /3 Axis Anti Shock 15G, 11ms duration
Ethernet	:	2 x RJ45 Broadcom BCM57780 GbE controller
Forsyning	:	+24Vdc in with 1.5KV DC isolation, Resistance (+9~36V DC input acceptable)
GPIO	:	8 x GPIO by Phoenix type Terminal Block
Grafik	:	Integrated in Intel NM10, LVDS/CRT
Hukommelse	:	1 x SODIMM, Max 4GB DDR3 800(2GB Default)
Luftfugtighed	:	5% to 95% (non condensing)





Svensk Binär Teknik

IPC-ATOM-D2550M

SPECIFICATIONS

Montering	:	default wall mount! Option VESA/Desktop
Msata	:	1 * 64 GB mSATA SSD
Porte	:	1 x RS232, 3 x Isolated RS422/485 auto-detected with Indicator
Udgange	:	VGA
Dimensioner	:	(L x W) 296mm x 169mm x 66mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.