

15" panel PC 6:e generationens i3 / i5 (tillval) processor med Touch IP66 front

FEATURES

- Bygg på beställning
- 15" TFT-LCD
- CPU i3 (i5-alternativ)
- Max. res. 1024x768
- Beröringsprojekterad Kapacitiv beröring
- 4 GB DDR4 RAM (max. 16 GB)
- 2 x USB
- 2 x RJ45 Lan
- 1 x RS232/422/485, 1 x RS232
- IP65 fram
- OS-stöd: Win. Embedded Compact 7,
Win 7/7 Pro, Win 7 Ultimate, Win Emb. 8.1 Industry
Pro
- Windows 10 IoT





SPECIFICATIONS

CPU	:	Onboard Intel 4th Gen. Core i3 CPU (option i5)
USB	:	2 x USB 3.0 type A
Driftstemperatur	:	temperature(°C) 0~50°C, -20~60°C (option)
Övrig	:	Optioner: 2 x CAN 2 x USB 2.0 type A + 1 x Mini-PCIe slot + 1xRS-232 DB-9 via TB-528C1U2P1, 2 x USB 2.0 type A , UPS battery 21W/10.8V/1.95Ah
Ethernet	:	2 x GbE LAN RJ-45
Forsyning	:	DC 9~36V 1 x 3-pin DC Power input terminal / 1 x 2-Pin Power Switch
Hukommelse	:	Onboard 4GB DDR4L / max 8GB
LCD	:	15" TFT-LCD Max. resolution 1024 x 768 Max. color 16.7M Luminance(cd/m ²) 420 Viewangle(H°/V°) 160/160 Backlight lifetime(hrs) 50,000
Luftfugtighed	:	10 to 90%@ 40°C, non-condensing
Lyd	:	1 x Audio Line Out
Montering	:	Panel Mounting / VESA 100 x 100
OS SUPPORT	:	Windows Embedded Compact 7, Windows Embedded Standard 7, Windows 7 Pro (FES) Windows 7 Ultimate (FES), Windows Embedded 8.1 Industry Pro, Windows 10 IoT





Svensk Binär Teknik

IPP15I3

SPECIFICATIONS

Touch	:	Projected Capacitive Touch, USB
Dimensioner	:	410mm x 310mm x 54.7mm



Binär Teknik AB
Lugna Gaten 39 Malmö, 211 59 Sweden



042 14 10 85



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.